

Parts		Club	
1	FRONT AXLE	AFM	WERA
2	REAR AXLE	SW	SW
3	AXLE PINCH BOLTS	SW OR R CLIPS WITH SW	SW OR R CLIPS
4	BODY WORK SECURED FIRMLY	SW (at least 1 bolt each side)	SW (at least 1 bolt each side)
5	FLUID RETAINING BELLY PAN	BIKES OIL CAPACITY	5QT
6	LIGHTS TAPED OR REMOVED	YES	YES
7	BRAKES FRONT & REAR	MUST WORK	MUST WORK
8	CALIPER BOLTS	SW	SW
9	ANCHOR ARMS	SW	SW
10	CABLES & HOSES	SILICONE(recommended)	SECURED
11	BRAKE PAD PINS	SECURED	R CLIPS,SW,SILICONE
12	SIDE CASES COVERS:model specific see rule books	CLUB SPECIFIC	CLUB SPECIFIC
13	VENTED CATCH TANK	YES	YES
14	CRANKCASE BREATHER TUBE:in catch or airbox	YES	YES
15	OIL DRAIN PLUG ENGINE:safety wired	YES	YES
16	OIL FILTER:secured with a hose clamp	YES	YES
17	OIL PRESSURE SWITCH	SILICONE, SW, EPOXY	SW,EPOXY
18	OIL FILLER CAP:wired or clip with wired properly	YES	YES
19	OIL LINE BOLTS EXCEPT TO OIL COOLER	SW,SILICONE, EPOXY	SW
20	OIL GALLEY BOLTS	SW,SILICONE, EPOXY	SW,EPOXY,SILICONE
21	FUEL LINES	CLAMPS OR SECURED	CLAMPS OR SECURED
22	FLUID RETAINING BOLTS	SILICONE, SW, EPOXY	SW,EPOXY
23	BOLTS & HOSES TO OIL COOLER	SW	SW
24	WATER JACKET DRAIN BOLTS	SW	SW
25	WATER PUMP DRAIN BOLTS	SW	SW
26	ANY FLUID LINE:hose clamp must be wired	SW (see other lines specific)	SW(only pressure lines)
27	HOSE CLAMPS	RECOMMEND SW	SW (on pressure lines)
28	RADIATOR CAP:wired or clip with wired properly	YES	YES
29	RADIATOR FLUID (non glycol based)	WATER WETTER	WW OR SILKOLENE
30	EXHAUST :see below	-	-
31	HEADER PIPE	SECURED	SW
32	REAR SUPPORT	SECURED	SW
33	EXHAUST BAFFLE	SW	SW
34	dB LIMIT: may be track specific	100-103	105
35	AMB X-260 TRANSPONDER	YES	YES
36	CLEAN BIKE	YES	YES
37	DRIVE CHAIN MASTER LINK	SW & SILICONE	SW & SILICONE
38	WHEELS:not cracked, spokes loose, etc	YES	YES
39	WHEEL WEIGHTS TAPED OVER	YES	YES
40	WHEEL: valve caps metal or plastic	METAL ONLY	YES
41	TIRES IN GOOD CONDITION	YES	YES
42	STEERING DAMPER REQUIRED	NOT SPECIFIED	YES
43	HANDLE BAR TANK CLEARANCE	YES	YES
44	HANDLE: bar ends, caps, or solid bars	YES	YES
45	BALL END ON LEVERS	YES	YES
46	SELF CLOSING THROTTLE	YES	YES
47	IGNITION KILL SWITCH:that works	YES	YES
48	SIGNALS OFF	YES	YES
49	PLASTIC LENSES TAPED	YES	YES
50	REMOVE LISENCE PLATE BRACKET	YES	YES
51	SIDE AND CENTER STANDS REMOVED	YES	YES
52	KICK START BOLTS:wired	SECURED	YES
53	2 CLUB DECALS (placed clearly on bike)	NO	YES
54	SPEEDO/TACH CABLES:wired	SECURED	YES
55	SHIFT PATTERN INDICATOR STICKER	NO	YES
56	FIRE EXTINGUISHER:5lb model in pits	YES	NOT SPECIFIED
57	NUMBER PLATES	White backgrounds with black numbers (unless you are a top 10 plate holders then you can reverse colors)	white backgrounds with black numbers (novice champ can run a red #1)
		5 1/2" numbers with a 1" stroke	4" high numbers
		front plate can be centered or on both sides	front plate must be centered(no side plates)
		rear number can be on top or both sides	rear numbers can be on both sides, if AMA style is used then number must be on belly pan as well.
		Fancy #1 is not permitted, must be straight #1 unless you are the champion	Fancy #1 is not permitted, must be straight #1 unless you are the champion
		10"x12" backgrounds	10"x12" backgrounds